



SUZUKI

Way of Life!

SUZUKI
KINGQUAD 450AX
4x4



Living Up To The KINGQUAD Badge

Sharing the award-winning attractions of Suzuki's flagship ATV - including purposeful styling, powerful engine performance, advanced electronic fuel injection, independent rear suspension, and locking front differential - the KINGQUAD 450AXi 4x4 offers class-leading value and performance, along with all-day comfort on the trail.

SUZUKI
KINGQUAD 450AXi
4x4



Terra Green (YLG)



Drive-mode switch



T-shaped seat



12V DC power outlet

- 454cm³, 4-stroke, liquid-cooled engine offers superb power from low to top end rpm range.
- Suzuki Plasma Spray Coating (SPSC) cylinder improves heat resistance while reducing weight.
- Light and rigid aluminum piston with an L-shaped top compression ring to increase ring sealing even at high rpm.
- Sportbike-derived, chain-and-gear camshaft drive system helps keep the engine compact.
- Fuel injection system featuring high-performance motorcycle's technology provides optimum, precise fuel charging under a wide range of running conditions.
- Electronic Control Module (ECM) efficiently regulates the fuel injection volume and ignition timing.

- Suzuki's QuadMatic CVT (Continuously Variable Transmission) features an efficient V-belt and centrifugal clutch to deliver the strong power to the ground.
- Advanced engine braking system to help control vehicle speed and minimize freewheeling.
- Gate-style drive range selector, to switch between low, high, neutral and reverse gears, for easy selection of gears.
- Unique torque-sensing limited-slip front differential offering more powerful traction as well as lighter steering effort.
- Convenient handlebar-mounted mode selection switch for choosing 2WD or 4WD, and also front differential-locked 4-wheel drive when completely stopped.

- Front differential lock system provides serious four-wheel-drive traction in even tough terrain conditions.
- Override switch on the left handlebars for overriding the normal speed limiter when stuck in the mud.
- Independent double wishbone front and rear suspension mated with a rear stabilizer bar provide excellent maneuverability and riding comfort.
- Easy-to-read digital LCD instrumentation for kph/mph-selectable speedometer, odometer, dual tripmeters, hour meter, clock, fuel gauge and drive mode indicator. LED warning lamps for fuel injection and engine temperature.

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

- Always wear a helmet, eye protection and protective clothing.
- Read your Owner's Manual carefully.
- PRINTED IN JAPAN KINGQUAD 450AXi 4x4 (LT-A450X) Leaflet 99999-A3202-1L1 SER.'09
- Enjoy riding safely.
- Never ride under the influence of alcohol or other drugs.

SUZUKI MOTOR CORPORATION
TAKATSUKA-CHO, MINAMI-KU, HAMAMATSU CITY, JAPAN

www.globalsuzuki.com

ATV SAFETY INFORMATION

The Suzuki KINGQUAD 450AXi 4x4 may be used only by those aged 16 and older. ATVs can be hazardous to operate. For your safety, always wear a helmet, eye protection and protective clothing. Always avoid paved surfaces. Never ride on public roads. Never carry passengers or engage in stunt riding. Riding and alcohol or other drugs don't mix. Avoid excessive speeds. Be extra careful on difficult terrain. Read your Owner's Manual carefully.

Specifications

Engine Type	4-stroke, 1-cylinder, liquid-cooled, SOHC	
Engine Displacement	454 cm ³ (cc)	
Bore x Stroke	84.0 mm x 82.0 mm	
Compression Ratio	10.0 : 1	
Transmission	V-belt, 2-speed with reverse	
Overall Length	2,115 mm (83.3 in.)	
Overall Width	1,210 mm (47.6 in.)	
Overall Height	1,215 mm (47.8 in.)	
Wheelbase	1,280 mm (50.4 in.)	
Ground Clearance	260 mm (10.2 in.)	
Seat Height	860 mm (33.9 in.)	
Curb Mass	305 kg (672 lbs.)	
Suspension	Front	Independent, double wishbone, coil spring, oil-damped
	Rear	Independent, double wishbone, coil spring, oil-damped
Brakes	Front	Disc, twin
	Rear	Sealed oil-bathed multi-disc
Tires	Front	AT25x8-12 ^{☆☆} , tubeless
	Rear	AT25x10-12 ^{☆☆} , tubeless
Ignition Type	Electronic ignition (CDI)	
Fuel Tank Capacity	17.5 L (4.6 US gal.)	

Colors



Flame Red (YT9)



Great Blue (YPW)



Realtree Hardwoods HD Enhanced (YVA)

100
YEARS OF INNOVATION

SUZUKI