



LT-A500F



The First True Sport Utility ATV


A good Sport Utility ATV combines the big value of a utility ATV with the great looks and performance of a sport ATV. The SUZUKI VINSON automatic 4x4 is like that, ready to work when there's a job to be done and ready to get away when the hard work is finished. Power from an advanced 493cc engine. Versatile, user-friendly automatic transmission. A light, slim chassis for maximum maneuverability. A host of convenient features. The VINSON automatic 4x4 is ready for both work and fun in a truly big way.



Terra Green (YLG)



Mode selection switch for 2WD and 4WD



Front storage compartment



Plastic skid plate

- 493cc, liquid-cooled, SOHC, 4-valve engine is designed to produce abundant low- to mid-range torque.

- The engine has vibration-reducing balancer shaft, high-capacity aluminum-alloy radiator and exhaust-valve decompressor.

- Suzuki Plasma Spray Coating (SPSC) cylinder is light and durable to provide efficient heat transfer.

- High-mounted snorkel-type air intake is positioned to foil water splashes.

- User-friendly QuadMatic automatic CVT (Continuously Variable Transmission) system is fully automatic to provide smooth, easy operation, and produce engine braking on down hills.

- Single convenient gearshift lever for high or low ranges, reverse, neutral and parking.

- Torque-sensing limited-slip front differential is light, compact, durable and efficient, allowing easy steering during four-wheel-drive operation.

- Spin-on type oil filter is easy to access for easy maintenance.

- Vacuum-operated fuel valve automatically turns the fuel flow on and off.

- SUZUKI's own T-shaped seat makes it easier for the rider to move back-and-forth or side-to-side when riding.

- Independent double wishbone front and swingarm type rear suspension with 5-way preload adjustable dual shock absorbers to help improving maneuverability.

- Front and rear disc brakes with single-piston caliper contribute to dependable stopping power.

- Easy-to-read digital LCD panel displays speedometer (kph/mph is selectable), odometer, dual trip meters, hour meter, clock, gear position indicator and separate indicators for 4WD and low.

- Dual 30/30W multi-reflector headlights, independent auxiliary light and large taillight with an integrated 21W brake light.

- Water-resistant 12V DC power outlet to plug electrically powered device.

Specifications

Engine Type	4-stroke, 1-cylinder, liquid-cooled, SOHC	
Engine Displacement	493 cm ³ (cc)	
Bore x Stroke	87.5 mm x 82.0 mm	
Compression Ratio	10.2 : 1	
Transmission	CVT with reverse, high/low 2-speed subtransmission	
Overall Length	2,095 mm (82.5 in.)	
Overall Width	1,170 mm (46.1 in.)	
Overall Height	1,235 mm (48.6 in.)	
Wheelbase	1,270 mm (50.0 in.)	
Ground Clearance	250 mm (9.8 in.)	
Seat Height	860 mm (33.9 in.)	
Dry Weight	274 kg (604 lbs.)	
Suspension	Front	Independent, double wishbone, coil spring, oil damped
	Rear	Swingarm type, coil spring, oil damped
Brakes	Front	Disc, twin
	Rear	Disc
Tires	Front	AT25x8-12 ☆☆, tubeless
	Rear	AT25x10-12☆☆, tubeless
Ignition Type	Electronic ignition (CDI)	
Fuel Tank Capacity	19.0 L (5.0 US gal.)	

Colors



Flame Red (YT9)



Solid Black No.2 (YLZ)

Specifications, appearances, equipments, colors, materials and other items of "SUZUKI" products shown on this catalogue are subject to change by manufacturers at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes. Actual body color might differ from the colors in this catalogue.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN VINSON 500 automatic 4x4 (LT-A500F) Leaflet 99999-A3102-171 JUL '06

SUZUKI MOTOR CORPORATION
 300 Takatsuka, Hamamatsu, Japan

www.globalsuzuki.com

ATV SAFETY INFORMATION

The SUZUKI VINSON automatic 4x4 may be used by those aged 16 and older. ATVs can be hazardous to operate. For your safety, always wear a helmet, eye protection and protective clothing. Always avoid paved surfaces. Never ride on public roads. Never carry passengers or engage in stunt riding. Riding and alcohol or other drugs do not mix. Avoid excessive speeds. Be extra careful on difficult terrain. Read your Owner's Manual carefully.

SUZUKI
 Ride the winds of change