

 **SUZUKI**



C90



An Unending Source Of Owner Pride

The way it looks. The way it sounds.

The way it feels. The SUZUKI BOULEVARD C90. Built for those who demand that a motorcycle be an unending source of owner pride. Relish it everywhere the spirit moves you.



Pearl Nebular Black (YAY)



Dual front brake



Well-padded low-slung seat



Multi-reflector headlight and turn signals

- 90 cubic-inch (1462cm³), air-cooled with Suzuki Advanced Cooling System (SACS), V-Twin engine produces massive torque at low engine rpm.

- Fuel injection ensures optimal fuel delivery, great throttle response and maximum power throughout the rpm range.

- High-precision digital ignition system incorporates automatic decompression system for easy starting.

- Hydraulic valve lash adjuster, a reliable shaft drive and a maintenance-free battery for low maintenance.

- Wide-ratio 5-speed transmission with an overdrive top gear.

- Hydraulically operated wet clutch has a back-torque limiter for smoother shift down.

- Double-cradle frame uses large-diameter, thin-wall main tubes for rigidity.

- 1.6-inch (41mm) front forks and a gas-charged single shock absorber rear suspension for sure-footed cruising.

- Hydraulic dual front disc brake with pin-slide 2-piston calipers and a single rear disc brake with opposed 4-piston calipers produce reliable stopping power.

- Well-padded low-slung seat, thick handgrips and broad floorboards together compose ready-to-cruise riding position.

- Removable passenger seat for full exposure of the rear fender.

- Front fork covers, mufflers and an air cleaner box make beautiful appearance and solid finish fully for ownership satisfaction.

- Convenient 3-liter storage compartment for small items.

- Center-mounted instruments including large speedometer with high-visibility LCD odometer, trip meter and fuel gauge.

Specifications

Engine Type	4-stroke, 2-cylinder, air-cooled, SOHC, 45° V-Twin	
Engine Displacement	1462 cm ³ (cc)	
Bore x Stroke	96.0 mm x 101.0 mm	
Compression Ratio	8.5 : 1	
Transmission	5-speed constant mesh	
Overall Length	2,525 mm (99.4 in.)	
Overall Width	1,000 mm (39.4 in.)	
Overall Height	1,130 mm (44.5 in.)	
Wheelbase	1,700 mm (66.9 in.)	
Ground Clearance	140 mm (5.5 in.)	
Seat Height	700 mm (27.6 in.)	
Curb Mass	320 kg (706 lbs.)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped, spring preload fully adjustable
Brakes	Front	Disc, twin
	Rear	Disc
Tires	Front	150/80-16 M/C 71H, tubeless
	Rear	180/70-15 M/C 76H, tubeless
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank Capacity	14.0 L (3.7 US gal.)	

Colors



Metallic Thunder Gray (YLF)

Specifications, appearances, equipments, colors, materials and other items of "SUZUKI" products shown on this catalogue are subject to change by manufacturers at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes. Actual body color might differ from the colors in this catalogue.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN SUZUKI BOULEVARD C90 (VL1500) Leaflet 99999-A0019-193 MAR.'08

SUZUKI MOTOR CORPORATION
 300 TAKATSUKA, MINAMI, HAMAMATSU, JAPAN

www.globalsuzuki.com

"SUZUKI BOULEVARD" is the model name mainly used for North American and Oceanian markets.



Way of Life!