

 **SUZUKI**



S50



Rumble Down The Boulevard In Style

The SUZUKI BOULEVARD S50 takes you cruising down the boulevard in sharp, handcrafted quality. Set yourself down in the thick, wide seat, and enjoy how this powerful engine rumbles along in the simple, uncluttered beauty of this machine. The gleaming front forks begin this bike's long flowing lines that lead to stylish rear fender. If you believe looks are as important as power, check the SUZUKI BOULEVARD S50 out.



Pearl Nebular Black (YAY)



Flat-type handlebars



Sleek, wide seat



Multi-reflector turn signals

- 805cm³, liquid-cooled, 45-degree V-Twin engine delivers strong low-to-mid rpm range torque.

- Digital ignition system with low-maintenance battery for optimum ignition timing throughout the engine rpm range.

- Clutch system with built-in spring-ramp system reducing spring pressure on the clutch plates under deceleration for smooth downshifting.

- MIKUNI 36mm (1.4in.) carburetors ensure lively throttle response and acceleration.

- Hydraulic valve adjusters and automatic cam chain tensioner for smooth quiet engine operation.

- Strong shaft drive and hydraulic clutch for low-maintenance yet high-tech operation.

- 33-degree raked front forks and sleek, wide seat with low 700mm (27.6in.) seat height supply comfortable ride.

- 19-inch front and 15-inch rear tires with classic spoked wheels.

- Custom flat-type handlebars for clean and sporty image.

- The sleek double-cradle frame and radiator cover are painted to match with the body color.

- High-quality, durable steel frame head cover, frame cover and front/rear fender.

- Easy-to-read speedometer, trip meter and indicator lamps.

- Convenient hazard and passing light switches.

- Multi-reflector turn signals for clear visibility.

Specifications

Engine Type	4-stroke, 2-cylinder, liquid-cooled, SOHC, 45° V-Twin	
Engine Displacement	805 cm ³ (cc)	
Bore x Stroke	83.0 mm x 74.4 mm	
Compression Ratio	10.0 : 1	
Transmission	5-speed constant mesh	
Overall Length	2,250 mm (88.6 in.)	
Overall Width	765 mm (30.1 in.)	
Overall Height	1,125 mm (44.3 in.)	
Wheelbase	1,560 mm (61.4 in.)	
Ground Clearance	125 mm (4.9 in.)	
Seat Height	700 mm (27.6 in.)	
Curb Mass	217 kg (479 lbs.)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Swingarm, coil spring, oil damped, spring preload 5-way adjustable
Brakes	Front	Disc
	Rear	Drum
Tires	Front	100/90-19M/C 57H, tube type
	Rear	140/90-15M/C 70H, tube type
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank Capacity	12.0 L (3.2 US gal.)	

Colors



Metallic Aqua Blue (YRB)

Specifications, appearances, equipments, colors, materials and other items of "SUZUKI" products shown on this catalogue are subject to change by manufacturers at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes. Actual body color might differ from the colors in this catalogue.

Always wear a helmet, eye protection, and protective clothing.
 Enjoy riding safely.
 Read your Owner's Manual carefully.
 Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN SUZUKI BOULEVARD S50 (VS800) Leaflet 99999-A0008-191 MAR.'08

SUZUKI MOTOR CORPORATION
300 TAKATSUKA, MINAMI, HAMAMATSU, JAPAN

www.globalsuzuki.com



Way of Life!