



Way of Life!

**TS185ER**



# At Home Over Roads Rough And Smooth

Let the TS185ER's power and well-proved, versatile design work for you.

Enjoy its functional and practical features that are built matched to the needs of day-to-day road and trails riding. You'll feel more at home on the TS185ER, whether the road is rough or smooth.

## TS185ER



Solid Special White No.2 (30H)



Stable 21-inch front tire



Functional engine guard plate



High-visible headlight and turn signals

- 183cm<sup>3</sup>, air-cooled, power-read-valve 2-stroke engine delivers high power, quick response and abundant usable torque with excellent fuel economy.

- Maintenance-free electronic ignition system delivers precise ignition at every engine rpm range.

- CCIS (Cylinder and Crank Injection System) assures necessary engine lubrication.

- 5-speed transmission with proper gear ratios chosen for smooth riding.

- Quick-action rack-and-pinion clutch design ensures light and positive clutch action.

- Lightweight and sturdy double-cradle steel-pipe frame.

- Combination of light 109kg curb mass, long-stroke suspensions, semi-knobby big tires and enough ground clearance keep the TS185ER moving over rough roads.

- Rear shock absorber comes with 5-way spring preload adjustment to fit various riding situations.

- Serrated footpegs and the brake pedal to prevent slipping in wet condition. Both of them and the gearshift lever are backward folding, aiming for less damage on the way with obstacles.

- A well-padded comfortable seat for rider and passenger whether the road is rough or smooth.

- A large headlight cover and the chrome-plated exhaust pipe protector accentuate the TS185ER's profile.

- An easy-to-read speedometer and tachometer.

## Specifications

Engine Type	2-stroke, 1-cylinder, air-cooled	
Engine Displacement	183 cm <sup>3</sup> (cc)	
Bore x Stroke	64.0 mm x 57.0 mm	
Compression Ratio	6.0 : 1	
Transmission	5-speed constant mesh	
Overall Length	2,160 mm (85.0 in.)	
Overall Width	860 mm (33.9 in.)	
Overall Height	1,125 mm (44.3 in.)	
Wheelbase	1,375 mm (54.1 in.)	
Ground Clearance	255 mm (10.0 in.)	
Seat Height	835 mm (32.9 in.)	
Curb Mass	102 kg (225 lbs.)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Swingarm type, coil spring, oil damped, spring preload 5-way adjustable
Brakes	Front	Drum
	Rear	Drum
Tires	Front	2.75-21 45P, tube type
	Rear	4.10-18 59P, tube type
Ignition Type	Electronic ignition (CDI)	
Fuel Tank Capacity	7.0 L (1.8 US gal.)	

## Colors



Solid Special White No.2 (30H)

Specifications, appearances, colors (including body color), equipments, materials and other aspects of the "SUZUKI" products shown on this leaflet are subject to change by SUZUKI at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

- Always wear a helmet, eye protection and protective clothing.
- Enjoy riding safely.
- Read your Owner's Manual carefully.
- Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN TS185ER Leaflet 99999-A1306-151 SEP'10

**SUZUKI MOTOR CORPORATION**

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

[www.globalsuzuki.com](http://www.globalsuzuki.com)