



Bandit 650 / *Bandit* 650A



Photo : Bandit 650A

A Fine Middleweight With Total Balance

The Bandit 650 / Bandit 650A offers high performance and smooth power delivery with its liquid-cooled inline-four cylinder featuring advanced SDTV fuel injection; an elegant styling exposing the engine; high value; user-friendly features like adjustable seat, handlebars and controls; and optional ABS. Pride of ownership comes standard.

Bandit 650 / Bandit 650A



Photo : Bandit 650

Pearl Suzuki Deep Blue No.2 (YBA)



ABS* (Bandit 650A only)



Convenient center stand



Streamlined headlight cover

- 656cm³, 4-cylinder, liquid-cooled, 4-valve-per-cylinder engine offering broad, responsive, smooth power and torque.
- The Bandit 650/A styling keeps the symmetrical-layout (center-cam-drive) engine well-exposed for ready admiration.
- Advanced, high-technology Suzuki Dual Throttle Valve (SDTV) fuel injection system effectively enhances smoothness of power delivery.
- Valvetrain with direct-acting camshafts for positive valve actuation at high rpm, and narrow-valve-angle design for better breathing.
- Friction-reducing chrome-nitride piston-ring coating.
- Automatic Idle Speed Control (ISC) system helps maintain stable idle and improves cold starting.

- Suzuki Pulsed-secondary AIR-injection (PAIR) system and other control systems allow the Bandit to meet tough Euro 3 emissions standards.
- 6-speed transmission, with a hydraulic clutch actuation system designed for an easy clutch-lever pull.
- ABS (Antilock Brake System) monitors brake lever input and wheel speed, and matches stopping power to available traction. (Bandit 650A only)*
- The double-cradle steel frame with thick downtubes is color-coordinated with the fuel tank and other body parts.
- 41mm-stanchion-tube front forks with a full 130mm of wheel travel and adjustable damping and spring preload.

- The handlebar position can be adjusted 10mm upward or downward.
- Seat height can be raised or lowered 20mm using reversible spacers.
- The clutch lever and front brake lever positions are 4-way adjustable.
- Bodywork accents include a streamlined cover behind the round multi-reflector headlight and a sculpted cover ahead of the fuel tank.
- Analog tachometer, LCD digital speedometer, LCD fuel gauge and clock, and LED indicator lamps.

Specifications, appearances, equipments, colors, materials and other items of "SUZUKI" products shown on this catalogue are subject to change by manufacturers at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes. Actual body color might differ from the colors in this catalogue.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN Bandit 650/A (GSF650/A) Leaflet 99999-A0107-181 SEP.'07

SUZUKI MOTOR CORPORATION
 300 TAKATSUKA, MINAMI, HAMAMATSU, JAPAN

www.globalsuzuki.com

*Please note that ABS is a supplemental device for brake operation, not a device for shortening stopping distance. Always remember to reduce speed sufficiently before approaching curves and corners.

Specifications

Engine Type	4-stroke, 4-cylinder, liquid-cooled, DOHC	
Engine Displacement	656 cm ³ (cc)	
Bore x Stroke	65.5 mm x 48.7 mm	
Compression Ratio	11.5 : 1	
Transmission	6-speed constant mesh	
Overall Length	2,130 mm (83.9 in.)	
Overall Width	780 mm (30.7 in.)	
Overall Height	Adjustable	1,085 / 1,095 mm (42.7 / 43.1 in.)
Wheelbase	1,470 mm (57.9 in.)	
Ground Clearance	135 mm (5.3 in.)	
Seat Height	Adjustable	770 / 790 mm (30.3 / 31.1 in.)
Dry Weight	Bandit 650/A	215 kg (473 lbs.) / 219 kg (482 lbs.)
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc, twin
	Rear	Disc
Tires	Front	120/70ZR17M/C (58W), tubeless
	Rear	160/60ZR17M/C (69W), tubeless
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank	19.0 L (5.0 US gal.)	

Colors

Photo : Bandit 650A



Metallic Oort Gray (YHG)



Pearl Nebular Black (YAY)



Candy Sonoma Red (YHL)

