



Way of Life!

GS500



Clear Your Schedule

The GS500 is an outstanding choice for an introductory sporting motorcycle with an all-round ability. The engine delivers invigorating power and plentiful torque. A natural, neutral steering makes for one good turn after another wherever you go, and easy round-town maneuverability. And well-padded seat and comfortable riding position are equally suited to cross-town commute and spirited rides on your favorite roads. Clear your schedule, and make time for an urgent appoint with the GS500.

GS500



Metallic Phantom Gray (YHF)



Rear disc brake



Sporty shaped 20-liter fuel tank



Bright headlight

- 487cm³, DOHC, parallel-twin engine with compact and low-maintenance design, built to produce useful accessible power over broad rpm range.

- Transistorized electronic ignition and precise carburetion help keep the engine running efficiently, and deliver plentiful torque at low rpm.

- Two-into-one exhaust system adds invigorating note to the engine's distinct pulses, yielding a good power delivery.

- Suzuki Pulsed-secondary AIR-injection (PAIR) system effectively keeps emissions low.

- Front telescopic forks and rear monoshock absorber both tuned for exciting combination of precise handling and supple ride.

- Easily accessible seven-way preload adjuster of rear suspension allowing quick tailoring to rider's preference.

- Front disc brake with two-piston caliper and rear disc brake provide excellent stopping power.

- Well-padded seat with enough seating space and comfortably positioned handlebars for easy in-town riding. Smooth seat surface for the rider to move around easily.

- 20-liter fuel tank, together with excellent engine fuel economy, means ample touring range.

- User-friendly features include comprehensive instrument cluster, convenient center stand and frame-mounted one-piece grab bar.

- Black-painted double-cradle frame, dark-silver engine finish and upswept tail section are visual reminders of the GS500's high sport-riding potential.

Specifications

Engine Type	4-stroke, 2-cylinder, air-cooled, DOHC	
Engine Displacement	487 cm ³ (29.7 cu. in)	
Bore x Stroke	74.0 mm x 56.6 mm	
Compression Ratio	9.0 : 1	
Transmission	6-speed constant mesh	
Overall Length	2080 mm (81.9 in)	
Overall Width	800 mm (31.5 in)	
Overall Height	1060 mm (41.7 in)	
Wheelbase	1405 mm (55.3 in)	
Ground Clearance	150 mm (5.9 in)	
Seat Height	790 mm (31.1 in)	
Curb Mass	193 kg (425 lbs)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc
	Rear	Disc
Tires	Front	110/70-17M/C 54H, tubeless
	Rear	130/70-17M/C 62H, tubeless
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank	20.0 L (5.3 US gal)	

Colors



Metallic Phantom Gray (YHF)

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN GS500 Leaflet 99999-A0103-121 SEP'11

SUZUKI MOTOR CORPORATION

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

