



Way of Life!

GS500F



A Recipe For Added Excitement

The GS500F's sports full fairing has expanded the horizons of Suzuki's already great all-rounder GS500. From looking great parked on the pavement to cutting through the urban crawl; from a touring holiday to a Sunday morning ride-out; the Suzuki GS500F will remind you why you love motorcycling. Go ahead. Stir things up on the Suzuki GS500F.

GS500F



Glass Splash White / Pearl Vigor Blue (CWH)



Vertically stacked headlights



Sharply styled slot to feed fresh air



Rear disc brake

- 487cm³, DOHC, parallel-twin engine with compact and low-maintenance design, built to produce useful accessible power over broad rpm range.
- Transistorized electronic ignition and precise carburetion help keep the engine running efficiently, and deliver plentiful torque at low rpm.
- Air-cooling oil cooler enhances engine reliability.
- Two-into-one exhaust system adds invigorating note to the engine's distinct pulses, yielding a good power delivery.
- Suzuki Pulsed-secondary AIR-injection (PAIR) system effectively keeps emissions low.

- Front telescopic forks and rear monoshock absorber are both tuned for exciting combination of precise handling and supple ride.
- Easily accessible seven-way preload adjuster of rear suspension allowing quick tailoring to rider's preference.
- Front disc brake with two-piston caliper and rear disc brake provide excellent stopping power.
- Specifically designed bodywork provides a low center of gravity and compliant suspension setup for excellent combination of sporty handling performance and smooth comfortable ride.

- Lightweight and modest 790mm (31.1in) seat height helps easy stop/go even in the city traffic.
- 20-liter fuel tank, together with excellent engine fuel economy, means ample touring range.
- Practical and sporty full fairing with sharp-styled slots and cutouts on the fairing provide comfortable ride.
- Racer-replica-inspired vertical high/low beam headlights with a positioning light below it.

Specifications

Engine Type	4-stroke, 2-cylinder, air-cooled, DOHC	
Engine Displacement	487 cm ³ (29.7 cu. in)	
Bore x Stroke	74.0 mm x 56.6 mm	
Compression Ratio	9.0 : 1	
Transmission	6-speed constant mesh	
Overall Length	2080 mm (81.9 in)	
Overall Width	800 mm (31.5 in)	
Overall Height	1150 mm (45.3 in)	
Wheelbase	1405 mm (55.3 in)	
Ground Clearance	120 mm (4.7 in)	
Seat Height	790 mm (31.1 in)	
Curb Mass	199 kg (439 lbs)	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc
	Rear	Disc
Tires	Front	110/70-17M/C 54H, tubeless
	Rear	130/70-17M/C 62H, tubeless
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank	20.0 L (5.3 US gal)	

Colors



Pearl Nebular Black / Metallic Phantom Gray (CZY)

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

- Always wear a helmet, eye protection and protective clothing.
- Enjoy riding safely.
- Read your Owner's Manual carefully.
- Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN GS500F Leaflet 99999-A0118-121 SER'11

SUZUKI MOTOR CORPORATION

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

