

**Specifications**

			3-door			5-door						
			Petrol		Diesel	Petrol		Diesel				
			1.3L	1.5L VVT	1.3L DDiS	1.3L	1.5L VVT	1.3L DDiS				
			4X2									
			LHD / RHD									
<b>DIMENSIONS</b>												
Overall length		mm	3,695									
Overall width		mm	1,690									
Overall height		mm	1,500									
Wheelbase		mm	2,380									
Tread	Front	mm	1,470									
	Rear	mm	1,480									
Ground clearance		mm	140									
Minimum turning radius		m	4.7									
Seating capacity		persons	4			5						
Luggage capacity	Rear seat folded (VDA method)	litres	(GA/GA-A):495 (GL/GL-A/GLX):561			(GA/GA-A):495 (GL/GL-A/GLX):561						
	Rear seat raised (VDA method)	litres	213									
<b>ENGINE</b>												
Type			M13A	M15A	Z13DT	M13A	M15A	Z13DT				
Number of cylinders			4	4	4	4	4	4				
Number of valves			16	16	16	16	16	16				
Piston displacement		cc	1,328	1,490	1,248	1,328	1,490	1,248				
Bore x stroke		mm	78.0 x 69.5	78.0 x 78.0	69.6 x 82.0	78.0 x 69.5	78.0 x 78.0	69.6 x 82.0				
Compression ratio			9.5	9.5	18	9.5	9.5	18				
Maximum output		kW/rpm	68/5,800	75/5,900	51/4,000	68/5,800	75/5,900	51/4,000				
Maximum torque		Nm/rpm	116/4,200	133/4,100	170/2,000	116/4,200	133/4,100	170/2,000				
Fuel distribution			Multipoint injection	Multipoint injection	Direct injection	Multipoint injection	Multipoint injection	Direct injection				
EU emission standard compliance			Euro 4									
<b>TRANSMISSION</b>												
Type			5MT	Automated 5MT	5MT	4AT	5MT	5MT	Automated 5MT	5MT	4AT	5MT
Gear ratio	1st		3.454	3.545	3.545	2.875	3.727	3.454	3.545	3.545	2.875	3.727
	2nd		1.904	1.913	1.904	1.568	1.960	1.904	1.913	1.904	1.568	1.960
	3rd		1.280	1.310	1.310	1.000	1.323	1.280	1.310	1.310	1.000	1.323
	4th		0.966	0.973	0.969	0.697	0.946	0.966	0.973	0.969	0.697	0.946
	5th		0.757	0.804	0.769	-	0.756	0.757	0.804	0.769	-	0.756
	Reverse		3.272	3.214	3.250	2.300	3.308	3.272	3.214	3.250	2.300	3.308
Final gear ratio			4.105	3.944	4.105	4.144	3.550	4.105	3.944	4.105	4.144	3.550
<b>CHASSIS</b>												
Steering			Rack & Pinion									
Brakes	Front		Ventilated disc									
	Rear		Drum, leading & trailing									
Suspensions	Front		MacPherson strut & coil spring									
	Rear		Torsion beam & coil spring									
Tyres			165/70R14, 185/60R15		185/60R15		165/70R14, 185/60R15		185/60R15			
<b>WEIGHTS</b>												
Curb weight (min.)/(with full option)		kg	970/1,030	980/1,040	980/1,040	1,000/1,060	1,045/1,105	990/1,050	1,000/1,060	1,000/1,060	1,020/1,080	1,065/1,125
Gross vehicle weight		kg	1,485			1,525			1,485			
<b>PERFORMANCE</b>												
Maximum speed		km/h	175	175	185	180	165	175	175	185	180	165
0-100 km/h		secs	11.0	12.5	10.0	11.7	14.2	11.0	12.5	10.0	11.7	14.2
<b>FUEL CONSUMPTION</b>												
Fuel tank capacity		litres	45									
Fuel consumption	CO <sub>2</sub> emissions	g/km	143	148	159	170	122	148	152	159	170	122
	Urban	litres/100km	8.0	7.8	8.6	9.3	5.7	8.0	8.0	8.6	9.3	5.7
	Extra-Urban	litres/100km	5.0	5.1	5.3	5.6	4.0	5.1	5.2	5.3	5.6	4.0
	Combined	litres/100km	6.1	6.1	6.5	6.9	4.6	6.2	6.2	6.5	6.9	4.6

Specifications may vary for individual markets.



Engine	Petrol									Diesel		
	1.3L			1.5L VVT			1.3L DDiS					
	GA	GA-A	GL	GL-A	GLX	GL	GL-A	GLX	GL	GL-A	GLX	
Grade	5MT			5MT / Automated 5MT			5MT / 4AT			5MT		
Transmission	LHD / RHD									3&5		
Steering	3-door / 4 persons, 5-door / 5 persons											
Number of doors												
Seating capacity												
<b>EXTERIOR</b>												
Halogen headlights	S	S	S	S	S	S	S	S	S	S	S	S
Headlamp levelling device	S	S	S	S	S	S	S	S	S	S	S	S
Muffler extension	-	-	-	-	-	S	S	S	S	S	S	S
Outside mirrors	Manually adjustable	S	S	S	S	S	S	S	S	S	S	S
	Electrically adjustable heated	*1	-	O	O	S	O	O	S	O	O	S
Coloured outside door mirror cowls	-	-	S	S	S	S	S	S	S	S	S	S
Coloured outside door handles	-	-	S	S	S	S	S	S	S	S	S	S
Tailgate opener	Key type	S	S	-	-	-	-	-	-	-	-	-
	Electromagnetic type	-	-	S	S	S	S	S	S	S	S	S
Windscreen wipers	2-speed + 1-speed intermittent	S	S	-	-	-	-	-	-	-	-	-
	2-speed + variable intermittent	-	-	S	S	S	S	S	S	S	S	S
Rear window intermittent wiper & washer	-	S	S	S	S	S	S	S	S	S	S	S
Rear window demister	-	S	S	S	S	S	S	S	S	S	S	S
Green tinted glass windows	-	S	S	S	S	S	S	S	S	S	S	S
Fog lamps	Front	-	-	O	O	S	O	O	S	O	O	S
	Rear	S	S	S	S	S	S	S	S	S	S	S
Black coloured A & B pillars	-	S	S	S	S	S	S	S	S	S	S	S
Tyres & wheels	165/70R14 + steel wheels (full wheel caps)	S	S	S	S	-	-	-	-	-	-	-
	185/60R15 + steel wheels (full wheel caps)	-	-	O	O	-	S	S	-	S	S	-
	185/60R15 + alloy wheels	-	-	O	O	S	O	O	S	O	O	S
<b>SAFETY &amp; SECURITY</b>												
Dual airbags	S	S	S	S	S	S	S	S	S	S	S	S
Side airbags (front seat mounted)	-	S	-	S	S	-	S	S	-	S	S	S
Front and rear curtain airbags	-	-	-	-	-	-	-	-	-	-	-	-
Head impact protection structure	S	S	S	S	S	S	S	S	S	S	S	S
Cold region specifications												
Seat heater (both front seats)	(LHD only)	-	-	-	O	O	-	O	O	-	O	O
Rear heater duct	-	-	-	-	-	-	-	-	-	-	-	-
PTC heater	-	-	-	-	-	-	-	-	-	-	-	-
Shift lock (AT & Automated 5MT)	-	-	S	S	S	S	S	S	-	-	-	-
Key interlock (AT only)	-	-	-	-	-	-	S	S	S	-	-	-
ABS with EBD	S	S	S	S	S	S	S	S	S	S	S	S
Brake assist	S	S	S	S	S	S	S	S	S	S	S	S
Decoupling pedal mechanism for brake & clutch pedals	S	S	S	S	S	S	S	S	S	S	S	S
Seat belts	Front:3-point ELR with pre-tensioner, force limiter & height adjuster	S	S	S	S	S	S	S	S	S	S	S
	Rear:3-point ELR	-	-	-	-	-	-	-	-	-	-	-
High mounted stop lamp	S	S	S	S	S	S	S	S	S	S	S	S
ISO-FIX child seat anchorages (2 rear seats)	S	S	S	S	S	S	S	S	S	S	S	S
Child seat tether anchorages (2 rear seats)	S	S	S	S	S	S	S	S	S	S	S	S
Child-proof rear door locks (5-door only)	S	S	S	S	S	S	S	S	S	S	S	S
Immobiliser	S	S	S	S	S	S	S	S	S	S	S	S
Freewheeling key cylinders	S	S	S	S	S	S	S	S	S	S	S	S
Deadlocks	-	-	S	S	S	S	S	S	S	S	S	S
Visible Vin (RHD only)	S	S	S	S	S	S	S	S	S	S	S	S
Daytime running lights (LHD only)	O	O	O	O	O	O	O	O	O	O	O	O
Side impact beams	S	S	S	S	S	S	S	S	S	S	S	S

Equipments and options may vary for individual markets.

\*1: 2 tweeters and electrically adjustable heated outside mirrors are set option for GL & GL-A.

\*2: For petrol MT and AT vehicles, 12V accessory socket is replaced by cigarette lighter.

For Automated 5MT & DDiS vehicles, cigarette lighter is fitted in the centre console box and 12V accessory socket is not removed.