

Description : **TANK PAD**

Part Number : 68100-2081\*


Applications : DS250

Installation Time : 0.25 H

**Contents**

**Items  
Provided  
by the  
Customer**
**Ref. Description**

- |     |  |
|-----|--|
| (1) | Degreasing agent<br>(Available at store) |
| (2) | Sponge                                   |



**Important**
**⚠ WARNING / ⚠ CAUTION / NOTICE / NOTE**

Please read this manual and follow its instructions carefully. To emphasize special information, the symbol **⚠** and the words **WARNING, CAUTION, NOTICE** and *NOTE* have special meanings. Pay particular attention to messages highlighted by these signal words:

**⚠ WARNING**

Indicates a potential hazard that could result in death or serious injury.

**⚠ CAUTION**

Indicates a potential hazard that could result in minor or moderate injury.

**NOTICE**

Indicates a potential hazard that could result in vehicle or equipment damage. ⇨ ⓘ

**NOTE**

*Indicates special information to make maintenance easier or instructions clearer. ⇨ ⓘ*

**Precautions  
for  
Installation**

1. Check that the kit includes all the parts listed on the first page.
2. Check each part in the kit for scratches or any form of damage.
3. Park the vehicle on a level ground.
4. Remove the ignition key from the switch and store it in a safe place.
5. Disconnect the negative (–) cable from the battery.
6. Protect any items removed or to be installed from scratches by placing them on a soft cloth first before putting them on the ground.
7. Use care not to cause any damage to the body of the vehicle during installation of the accessory.

**Installation** Attach the Pads as following illustration.



- Clean and degrease the attaching area of the Pads.
- Do not use an organic solvent for degreasing of body parts.

